

STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Aero-Tech

2900 Gary Drive Plymouth IN 46563 **ACTIVE**

								TOTAL		
TANK NUMBER	CATEGORY	WALL	LIQUID DEPTH		CTERIOR LENGTH	IN-OUT DROP	EFFECTIVE GALLONS	GALLONS (Pump Tanks) U	APPROVAL SE DATE	FAMILY
70-147-AT2-0	C3 C3	0.25	66.00	64	64		835	ATU	7/6/2010	
	rglass. Houses to AT-750 ATU		500 gallon	per day A	TU. Requir	es 500 gal	lon minimum p	oretreatment tank. V	V/o clarifier can l	oe pretreatment
70-147-AT3-0	C3 C3	0.25	66.00	64	64		835	ATU	7/6/2010	
	rglass. Houses to AT-750 ATU		600 gallon	per day A	TU. Requi	res 600 ga	ıllon minimum	pretreatment tank. \	W/o clarifier can	be pretreatment
70-147-AT4-0	C3 C3	0.25	66.00	72	72		1050	ATU	7/6/2010	
	rglass. Houses to AT-1000 ATI		-750 gallor	ns per da	y ATU. Red	quires 750	gallon minimui	m pretreatment tanl	k. W/o clarifier ca	an be pretreatment
70-147-AT5-0	C3 C3	0.25	66.00	84	84		1450	ATU	7/6/2010	
REMARKS: Fibe	rglass. Houses	Aero-Tech AT-	1000 gallor	ns per da	y ATU. Red	quires 1000	gallon minimi	um pretreatment tar	nk.	
70-147-AT6-0	C3 C3	0.25	72.00	96	96		2100	ATU	12/20/2010	

REMARKS: Fiberglass. Houses Aero-Tech AT-1500 gallons per day ATU. Requires 1500 gallon minimum pretreatment tank.



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Alpha General Services, Inc.

Highlands

Post Office Box 3331 Sebring, FL 33871 ACTIVE

TOTAL

WALL LIQUID TOP EXTERIOR IN-OUT EFFECTIVE GALLONS APPROVAL

TANK NUMBER CATEGORY THICKNESS DEPTH WIDTH LENGTH DROP GALLONS (Pump Tanks) USE DATE FAMILY

28-004-18S-C3 C3 0.25 50.00 69.5 124.5 1300 1,552 ATU 3/22/2002

REMARKS: for use with Bio-Microbics ATUs MicroFAST 0.5, when used with 350gal min. settling tank; MicroFAST 0.75 when used with a 375 gal min. settling tank; MicroFAST 0.9 when used with a 500 gal min. settling tank; all in lid installation; no mid-seam test after install needed with Alpha sticker;

28-004-BM1-C3 C3 0.25 49.00 69.5 124.5 1300 1,552 ATU 2/6/2008

REMARKS: slide-in baffle located for use with Bio-Microbics ATUs MicroFAST 0.5; MicroFAST 0.75; MicroFAST 0.9; all in lid installation; no mid-seam test

after install needed with Alpha sticker;



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

AquaKlear, Inc.

870 Bierdeman Road Pearl MS 39208

TOTAL	

		WALL	LIQUID	TOP E	XTERIOR	IN-OUT	EFFECTIVE	GALLONS	A	APPROVAL	_
TANK NUMBER	CATEGORY	THICKNESS	DEPTH	WIDTH	LENGTH	DROP	GALLONS	(Pump Tanks)	USE	DATE	FAMILY
		0.05	50.50								
70-114-05-C3	C3	0.25	50.50							12/30/2004	1
REMARKS: fiberg	lass tank-hous	es the 500 gall	on per day <i>i</i>	AquaKlea	ar ATU						
70-114-06-C3	C3	0.31	55.00							5/24/2002	2
REMARKS: fiberg	lass tank-hous	es the 600 gall	on per day	AquaKlea	ar ATU						
70-114-08-C3	C3	0.38	56.50							12/30/2004	1
REMARKS: fiberg	lass tank-hous	es the 800 galle	on per day	AquaKlea	ar ATU						
70-114-10-C3	C3	0.44	56.50							12/30/2004	1
REMARKS: fiberg	lass tank-hous	es the 1000 ga	llon per day	AquaKle	ear ATU						
70-114-15-C3	C3	0.44	68.00	65	136					12/5/2006	6
REMARKS: fiberg	lass tank-hous	es the 1500 ga	llon per day	AquaKle	ear ATU						
70-114-75-C3	C3	0.38	56.50							12/30/2004	1
REMARKS: fiberg	lass tank-hous	es the 750 galle	on per day	AquaKlea	ar ATU						



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Baker Septic Installations, Inc.

Highlands

7740 South George Blvd. Sebring, FL 33875

ACTIVE

5						TOTAL	
	WALL	LIQUID	TOP EXTERIOR	IN-OUT	EFFECTIVE	GALLONS	APPROVAL

TANK NUMBER	CATEGORY	THICKNESS	DEPTH	WIDTH	LENGTH	DROP	GALLONS	(Pump Tanks) US	SE DATE	FAMILY
28-031-AK10-	C3 C3	3.00	50.50	50	139.5		1000	ATU	9/5/2012	
	in baffle. Hous (10S245C Aqua		300C or AK	800CA A	quaKlear Al	ΓU. With	705 gallon min	imum pretreatment t	ank, houses 10	00 gpd AK10PTC
28-031-AK6-C	;4 ^{C4}	3.00	50.50	50	139.5		1000	ATU	9/5/2012	
REMARKS: mono	olithic baffleHo	ouses 600 gpd /	AK6PT, AK	6PTC or	AK6S245C	AquaKlea	ır ATU			
28-031-DF50-	C4 C4	3.00	51.50	78	78		900	ATU	6/21/2010	
REMARKS: Circu	lar tank-House	s Delta 500 gpc	I DF50-CA	ATU						
28-031-11-03	C3	3.00	50.00	59	120		1160	1.494 ATU	10/30/2006	

REMARKS: Mid-seam tank, Houses Jet Models J-500 thru J-1500 ATU's. J-500, J-600, J-750 without pretreatment tank; J-1000, J-1250, J-1500 with minimum 1000 gallon pretreatment tank.



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Bingham Onsite Precasting Inc.

REMARKS: Used to house the Mighty Mac 600 ATU

Polk

6172 Highway 640 West Mulberry FL 33830

		WALL	LIQUID	TOP EXT	ERIOR	IN-OUT	EFFECTIVE	GALLONS	APPROVAL
TANK NUMBER	CATEGORY	THICKNESS	DEPTH	WIDTH I	LENGTH	DROP	GALLONS	(Pump Tanks) USE	DATE FAMILY
53-137-71S-C3	3 C3	3.50	73.00				4000	4,755 B, ATU	3/22/2002
REMARKS: For us	e with Bio-Mic	robics enginee	red ATUs:	MicroFAST	√ 4.5 low-p	orofile leg i	nstallation with	pretreatment tank and	d three-hole lid of GT3 tank
53-137-A1-C3	C3	3.00					500	ATU	3/22/2002
REMARKS: Used	to house the A	Iliance ATU							
53-137-C/A-C3	C3	3.00	52.50				750	ATU	3/22/2002
REMARKS: Used	to house the C	ajun-Aire 500 8	& 750 ATU						
53-137-MM1-C	;4 ^{C4}	0.38	66.00					ATU	3/22/2002
REMARKS: Used	to house the M	lighty Mac 500	ATU						
53-137-MM2-C	;3 C3	0.38	66.00					ATU	10/6/2002
REMARKS: Used	to house the M	lighty Mac 750	ATU						
53-137-MM3-C	;3 C3	0.38	66.00					ATU	10/6/2002



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS

SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Bonded Septic Tank

P.O. Box 1509-State Rd 486 Hernando, FL 34442 Citrus

ACTIVE

TOTAL

WALL LIQUID <u>TOP EXTERIOR</u> IN-OUT EFFECTIVE GALLONS APPROVAL
TANK NUMBER CATEGORY THICKNESS DEPTH WIDTH LENGTH DROP GALLONS (Pump Tanks) USE DATE FAMILY

3.00 43.25 120.5 1114 1,337 64 6/3/2008 09-030-11D-C3 REMARKS: Used to house Bio-Microbics MicroFAST 0.5 and 0.75 ATU. C3 3.00 43.25 120.5 1138 1,337 09-030-11S-C3 6/3/2008

REMARKS: When used with a 450 to 900 gallon settling tank used to house Bio-Microbics MicroFAST 0.9 ATU. Also, when used with a 750 to 1500 gallon settling tank, used to house Bio-Microbics MicroFAST 1.5 ATU.



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Bord na Mona

P.O. Box 77457 ACTIVE

Greensboro NC 27417

TOTAL

WALL LIQUID <u>TOP EXTERIOR</u> IN-OUT EFFECTIVE GALLONS APPROVAL

TANK NUMBER CATEGORY THICKNESS DEPTH WIDTH LENGTH DROP GALLONS (Pump Tanks) USE DATE FAMILY

70-130-01S-TM TM 0.25 3/30/2005

REMARKS: Polyethylene tank used to house 12" above ground 7'L x 4.5'W x 2.5'D Puroflo Peat Biofilter ATU



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Brooks Concrete

ATU

Wakulla

ACTIVE

P. O. Box 82

1 . O. BOX 02									7.011	ν		
Panacea, FL 3	2346								TOTAL			
TANK NUMBER	R CATEG		WALL IICKNESS	LIQUID DEPTH		(TERIOR LENGTH	IN-OUT DROP	EFFECTIVE GALLONS	GALLONS (Pump Tanks)	USE	APPROVAL DATE FAMILY	
65-073-BM	1-C3	C3	2.50	40.50	60	102		850	AT	U	9/12/2007	
			hortened Mic 0.9). Modific				or MicroFAS	ST 0.9 ATU. S	ettling tanks requ	uired	(350-500gal for 0.5; 375-	-750ga
65-073-BM2	2-C3	C3	2.50	42.88	60	102		900	AT	U, s	10/15/2007	
			nk with two se hole at 24 in a						use as dual com MicroFAST 0.5 A		nent septic tank; baffle w n lid installation.	ith
65-073-BM3	3-C3	C3	2.50	40.50	60	119		900	AT	U	11/19/2007	
REMARKS: m	onolithic baff	le set to	house Bio-Mi	crobics sh	ortened N	/licroFAST	0.5 ATU					
65-073-NW	1-C3	C3	2.50	54.00							12/24/2001	
	orweco (Sing er day ATU.	ulair 960	and Singulaii	r TNT mod	del) 500/6	00 gallon p	er day ATI	J. Add 1000 g	allon pretreatme	nt cha	amber to become 1000 g	jallon
65-073-NW	2-C3	C3	2.50	66.00							8/28/2002	
	orweco (Sing TU.	ulair 960	and Singulaii	r TNT mod	del) 750/8	00 gallon p	er day ATI	J. Add 1250 p	retreatment char	nber	to become 1250 gallon p	er day
65-073-NW	3-C3	C3	3.00	53.00	72	111			AT	U	4/30/2007	
REMARKS: H	ouses Norwe	co (Singı	ulair 960 and	Singulair T	ΓNT mod	el) 500 and	600 gpd A	TU's. Also, wit	h 1000 gallon pro	etreat	ment tank it houses 100	0 gpd



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Caribe Jet, Inc.

Polk

ACTIVE

4753 E. Highway 92 Lakeland FL 33801

TOTAL

WALL LIQUID <u>TOP EXTERIOR</u> IN-OUT EFFECTIVE GALLONS APPROVAL

TANK NUMBER CATEGORY THICKNESS DEPTH WIDTH LENGTH DROP GALLONS (Pump Tanks) USE DATE FAMILY

53-131-J1-C3 C3 3.00 50.00 1160 1,494 ATU 8/22/2005

REMARKS: Houses Jet Models J-500 thru J-1500 ATU's



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS

SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Cast Systems LLC.

Charlotte

19400 Peachland Blvd. Port Charlotte FL 33954

	WALL	LIQUID	TOP EXTERIOR	IN-OUI	EFFECTIVE	GALLONS	Α	PPROVA	L
TANK NUMBER	CATEGORY THICKNESS	DEPTH	WIDTH LENGT	H DROP	GALLONS	(Pump Tanks)	USE	DATE	FAMILY

08-123-AK1-C3	C3	3.00	51.00	750	ATU	2/11/2003
REMARKS: used to house	the AquaKle	ear AK500S	96F ATU			
08-123-DF50-C3	C3	3.00	52.25	919	1,057 ATU	7/2/2003
REMARKS: used to house	the Delta W	hitewater D	F50-CA or UC50-CA ATU			



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016

in date: 11/9/2016
Searching for: ATU

Clearstream Wastewater Systems, Inc.

WALL

P.O. Box 7568

LIQUID

Beaumont TX 77726-7568

TOTAL

<u>TOP EXTERIOR</u> IN-OUT EFFECTIVE GALLONS APPROVAL

TANK NUMBER	CATEGORY	THICKNESS	DEPTH	WIDTH	LENGTH	DROP	GALLONS	(Pump Tan	ks) USE	DATE	FAMILY
70-120-05N-C	3 C3	0.25	63.00						ATU	11/5/2002	
REMARKS: Fibero	glass tank-hous	es Clearstream	500 gallor	n per day	ATU						
70-120-06N-C	3 C3	0.31	55.00						ATU	11/5/2002	
REMARKS: Fiberç	glass tank-hous	es Clearstream	600 gallor	n per day	ATU						
70-120-07N-C	3 C3	0.31	65.00						ATU	11/5/2002	
REMARKS: Fiberç	glass tank-hous	es Clearstream	750 gallor	n per day	ATU						
70-120-10N-C	3 C3	0.38	87.00						ATU	11/5/2002	
REMARKS: Fiberç	glass tank-hous	es Clearstream	1000 gallo	on per da	y ATU						
70-120-15N-C	3 C3	0.44	82.00						ATU	11/5/2002	
REMARKS: Fiberç	glass tank-hous	es Clearstream	1500 gallo	on per da	y ATU						
70-120-25A-C	3 C3	0.25	55.00	79	79	0	850	1,000	ATU	10/19/2015	1
REMARKS: Fiberç	glass Midseam	500NST; used	to house 5	00 gpd A	TU Clearstr	eam 500N					
70-120-25A-C	4 C4	0.25	55.00	79	79	0	850	1,000	ATU	10/19/2015	2
REMARKS: Fiberç	glass Midseam	500NST; used	to house 5	00 gpd A	TU Clearstr	eam 500N					
70-120-25AB-	C4 C4	0.25	55.00	79	79	0	850	1,000	ATU	10/19/2015	2
REMARKS: Fiberç	glass Midseam	500NST-B; use	d to house	500 gpc	I ATU Clear	stream 500l	N				
70-120-25AB-0	C3 C3	0.25	55.00	79	79	0	850	1,000	ATU	10/19/2015	1
REMARKS: Fiber	glass Midseam	500NST-B; use	d to house	500 gpd	I ATU Clear	stream 500l	N				
70-120-26A-C	3 C3	0.25	55.00	88	88	0	1050	1,250	ATU	10/19/2015	3
REMARKS: Fiber	glass Midseam	600NT; used to	house 600	gpd AT	U Clearstre	am 600N					
70-120-26A-C	4 C4	0.38	55.00	88	88	0	1050	1,250	ATU	10/19/2015	4
REMARKS: Fiberç	glass Midseam	600NT; used to	house 600	gpd AT	U Clearstre	am 600N					
70-120-26AB-0	C4 C4	0.38	55.00	88	88	0	1050	1,250	ATU	10/19/2015	4
REMARKS: Fiberç	glass Midseam	600NT-B; used	to house 6	600 gpd /	ATU Clearst	ream 600N					
70-120-26AB-0	C3 C3	0.25	55.00	88	88	0	1050	1,250	ATU	10/19/2015	3
REMARKS: Fiberç	glass Midseam	600NT-B; used	to house 6	600 gpd /	ATU Clearst	ream 600N					
70-120-27A-C	4 C4	0.44	65.00	88	88	0	1250	1,450	ATU	10/19/2015	6
REMARKS: Fiberç	glass Midseam	750NT; used to	house 750	gpd AT	U Clearstre	am 750N					
70-120-27A-C	3 C3	0.25	65.00	88	88	0	1250	1,450	ATU	10/19/2015	5
REMARKS: Fiber	glass Midseam	750NT; used to	house 750	gpd AT	U Clearstre	am 750N					
70-120-27AB-0	C4 C4	0.44	65.00	88	88	0	1250	1,450	ATU	10/19/2015	6
REMARKS: Fiberç	glass Midseam	750NT-B; used	to house 7	750 gpd /	ATU Clearst	ream 750N					
70-120-27AB-0	C3 C3	0.25	65.00	88	88	0	1250	1,450	ATU	10/19/2015	5
REMARKS: Fiberç	glass Midseam	750NT-B; used	to house 7	750 gpd /	ATU Clearst	ream 750N					



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

TOP EXTERIOR IN-OUT EFFECTIVE GALLONS

Consolidated Treatment Systems, Inc.

WALL

1501 Commerce Center Drive ACTIVE

LIQUID

Franklin OH 45005

TOTAL

APPROVAL

TANK NUMBER	CATEGORY THICK	IESS DEPTH WIDTH	LENGTH DROP	GALLONS (Pump	Tanks) USE	DATE FAMILY
70-113-EG1-C	C3	64.00				2/25/2005
REMARKS: fiberg	lass-houses Enviro-Gua	ard 750 gpd ATU				
70-113-MF1-C	C3 C3	54.00				5/20/2002
REMARKS: fiberg	lass-houses MULTI-FL0	O FTB 0.5 (500 gpd) ATU				
70-113-MF2-C	C3	54.00				5/20/2002
REMARKS: fiberg	lass-houses MULTI-FL0	O FTB 0.6 (600 gpd) ATU				
70-113-MF3-C	C3	58.00				5/20/2002
REMARKS: fiberg	lass-houses MULTI-FL0	O FTB 0.75 (750 gpd) ATU				
70-113-MF4-C	C3	64.00				5/20/2002
REMARKS: fiberg	lass-houses MULTI-FL0	O FTB 1.0 (1000 gpd) ATU				
70-113-MF5-C	C3	54.00				5/20/2002
REMARKS: fiberg	lass-houses MULTI-FL0	O FTB 1.5 (1500 gpd) ATU				
70-113-N1-C3	C3	62.50				5/20/2002
REMARKS: fiberg	lass-houses NAYADIC	M6-A (500 gpd) ATU				
70-113-N1A-C	:3 C3	0.19 62.50 72	72	500	ATU	1/26/2012
REMARKS: fiberg	lass-houses NAYADIC	M6-A (500 gpd) ATU				
70-113-N2-C3	C3	68.00				5/20/2002
REMARKS: ffiber	glass-houses NAYADIC	M8-A (600 gpd) ATU				
70-113-N3-C3	C3	75.50				5/20/2002
REMARKS: ffiber	glass-houses NAYADIC	M1050-A (800 gpd) ATU				
70-113-N4-C3	C3	86.00				5/20/2002
REMARKS: fiberg	lass-houses NAYADIC	M1200-A (1000 gpd) ATU				
70-113-N5-C3	C3	96.50				5/20/2002
REMARKS: fiberg	lass-houses NAYADIC	M2000-A (1500 gpd) ATU				



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Del Zotto Mfg. Co.

4575 W. Highway 40 Ocala, FL 34482 Marion

ACTIVE

TOTAL

		WALL	LIQUID			IN-OUT	EFFECTIVE	GALLONS APPROVAL			L
TANK NUMBER	CATEGORY	THICKNESS	DEPTH	WIDTH	LENGTH	DROP	GALLONS	(Pump Tanks)	USE	DATE	FAMILY
42-007-08D-C	3 C3	2.50	42.00				1050			11/13/200	2
REMARKS: House	es Bionest BN	C-400 ATU.									
42-007-08D-C	4 C4	4.00	42.00				1050			11/13/200	2
REMARKS: House	es Bionest BN	C-400 ATU.									
42-007-30D-C	3 C3	4.00	42.00				1900			2/4/200	2
REMARKS: House	es Bionest BN	C-750 ATU.									
42-007-49D-C	3 C3	4.00	60.00				2700			2/4/200	2
REMARKS: House	es Bionest BN	C-1000 ATU.									
42-007-CS1-C	3 C3	3.00	57.00	0	0			AT	Ū	6/6/200	7
REMARKS: Monol	lithic tank-Hoເ	ıses 600 gpd C	learstream	Model 60	ONC3T ATU	J					
42-007-JT1-C	1 C4	3.00	52.38	61.63	123			AT	Ū	1/15/200	9
REMARKS: Used	to house the J	et 500 and 750	GPD ATU.	With pre	etreatment t	ank, used	to house Jet 1	000, 1250, and 1	500 G	PD ATU	



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Delta Environmental Products, Inc.

P.O. Box 969

Denham Springs LA 70727

TOTAL

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH		CTERIOR LENGTH	IN-OUT DROP	EFFECTIVE GALLONS	GALLONS (Pump Tanks) USI	APPROVAL E DATE	FAMILY
70-115-DF1-C	3 C3	0.31	51.56	72	72			ATU	6/11/2002	2 1
REMARKS: Fiberg	lass tank-Hou	ses Delta DF50)-FF or UC5	0-FF AT	U @ 500 gp	od				
70-115-DF2-C	3 C3	0.31	59.50	75	75			ATU	6/11/2002	2 2
REMARKS: Fiberg	lass tank-Hou	ses Delta DF60)-FF or UC6	60-FF AT	U @ 600 gp	od				
'0-115-DF3-C	3 C3	0.38	64.00	81	81			ATU	6/11/2002	2 3
REMARKS: Fiberg	lass tank-Hou	ses Delta DF75	5-FF or UC7	75-FF @ 1	750 gpd, or	UC90-FF	ATU @ 900 gp	od		
'0-115-DF4-C	3 C3	0.38	61.00	96	96			ATU	6/11/2002)
EMARKS: Fiberg	lass tank-Hou	ses Delta DF10	00A-FF or U	IC100A-F	F ATU @ 1	000 gpd				
0-115-DF5-C	3 C3	0.38	91.50	96	96			ATU	6/11/2002)
EMARKS: Fiberg	lass tank-Hou	ses Delta DF15	50-FF or UC	150-FF	ATU @ 150	00 gpd				
0-115-E0-C3	C3	0.31	48.00	66	66		710	ATU	5/30/2012	2 1
EMARKS: Fiberg	lass tank-Hou	ses 500 gpd De	elta E50-N	ATU; requ	uires at leas	t 500 gallo	on pretreatmen	t tank		
0-115-E1A-C	3 C3	0.31	48.00	72	72		840	ATU	5/30/2012	2 1
EMARKS: Fiberg	lass tank-Hou	ses 500 gpd De	elta E50-N	ATU (out	let changed	l compare	d to DF1); requ	ires at least 500 gallo	on pretreatme	nt tank
0-115-E1B-C	3 C3	0.31	52.00	72	72		916	ATU	5/30/2012	2 1
EMARKS: Fiberg	lass tank-Hou	ses 600 gpd De	elta E60-N	ATU (outl	et changed	compared	d to DF1); requ	ires at least 600 gallo	on pretreatme	nt tank
0-115-E2-C3	C3	0.31	57.00	75	75		1100	ATU	5/30/2012	2 2
EMARKS: Fiberg	lass tank-Hou	ses 750 gpd De	elta E75-N	ATU (outl	et changed	compare	d to DF2); requ	ires at least 750 gallo	on pretreatme	nt tank
0-115-E3-C3	C3	0.38	63.00	81	81		1400	ATU	5/30/2012	2 3
EMARKS: Fiberg	lass tank-Hou	ses 1000 gpd D	Delta E100-	N ATU (o	utlet chang	ed compar	red to DF3); red	quires at least 1000 g	allon pretreati	ment tank



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Ecological Tanks, Inc.

REMARKS: Houses the Aqua Safe 750 ATU

2247 Highway 151 N. Downsville LA 71234

Downsville LA 712	234							TOTAL			
		WALL	LIQUID	TOP E	XTERIOR	IN-OUT	EFFECTIVE	GALLONS		APPROVAL	
TANK NUMBER	CATEGORY	THICKNESS	DEPTH	WIDTH	LENGTH	DROP	GALLONS	(Pump Tan	ks) USE	DATE	FAMILY
70-125-AS10-0	C3 C3	0.47	90.00						ATU	6/3/2003	
REMARKS: House	es the Aqua Sa	afe 1000 ATU									
70-125-AS15-0	C3 C3	0.47	90.00						ATU	6/3/2003	
REMARKS: House	es the Aqua Sa	afe 1500 ATU									
70-125-AS5-C	3 C3	0.40	67.50						ATU	6/3/2003	
REMARKS: House	es the Aqua Sa	afe 500 ATU									
70-125-AS5L-0	C3 C3	0.30	51.50	79	79	2.5	908	1,048	ATU	1/13/2016	1
REMARKS: House	es the Aqua Sa	afe AS500L 500	gpd ATU								
70-125-AS6-C	3 C3	0.40	67.50						ATU	6/3/2003	
REMARKS: House	es the Aqua Sa	afe 600 ATU									
70-125-AS6L-0	C3 C3	0.30	60.50	79	79	2.5	1058	1,198	ATU	1/13/2016	1
REMARKS: House	es the Aqua Sa	afe AS600L 600	gpd ATU								
70-125-AS7-C	3 C3	0.45	67.50						ATU	6/3/2003	



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS

SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

TOP EXTERIOR IN-OUT EFFECTIVE GALLONS

Florida Septic,Inc.

WALL

LIQUID

Post Office Box 545 Hawthorne, FL 32640 Alachua

ACTIVE

APPROVAL

TOTAL

TANK NUMBER	CATEGORY TH	IOITINEGO	DEPTH V		-		GALLONS (I	p	SE DATE	I AMIL I
01-011-07S-C	3 C3	2.50	51.75				1050	B+ AT	6/11/2002	!
REMARKS: Can be	e used to house B	io-Microbics	MicroFAST	0.5 ATL	J when used	with 350 ga	allon min. settl	ing tank		
01-011-09D-C	3 C3	2.50	50.00				1050		1/31/2001	
REMARKS: House	s Bionest BNC-40	00 ATU								
01-011-11D-C	4 C4		44.00				1050	1,348	3/17/2003	}
REMARKS: House	s Bionest BNC-40	00 ATU. Wa	all thickness	can be	either 4" or 0	6". AASHT	O HS20 traffic	loading rated whe	en buried betwe	en 18" to 48"
01-011-13D-C	4 C4		52.00				1250	1,564	3/17/2003	}
REMARKS: House	s Bionest BNC-50	00 ATU. Wa	ll thickness	can be	either 4" or 6	". AASHTO) HS20 traffic	loading rated whe	n buried betwe	en 18" to 48"
01-011-20D-C	3 C3	3.00	63.00				1500		5/31/2001	
REMARKS: House	s Bionest BNC-60	00 ATU.								
01-011-23D-C	1 C4	4.00	53.00				1500		7/30/2001	
REMARKS: House	s Bionest BNC-60	00 ATU								
01-011-27D-C	4 C4	6.00	53.00				1500		10/31/2001	
REMARKS: House	s Bionest BNC-60	00 ATU. AAS	HTO HS20	traffic lo	pading rated	when burie	d between 18"	to 48"		
01-011-37D-C	3 C3	3.00	53.00				2000		7/30/2001	
REMARKS: House	s Bionest BNC-75	50 ATU								
01-011-38D-C	4 C4	4.00	53.00				2000		7/30/2001	
REMARKS: House	s Bionest BNC-75	50 ATU								
01-011-39D-C	4 C4	6.00	53.00				2000		5/29/2002	
REMARKS: House	s Bionest BNC-75	0 ATU. AAS	HTO HS20	traffic lo	pading rated	when burie	d between 18"	to 48"		
01-011-43D-C	4 C4	4.00	66.00				2500		7/30/2001	
REMARKS: House	s Bionest BNC-10	000 ATU								
01-011-64D-C	3 C3	4.00	50.00				3300		8/14/2001	
REMARKS: House	s Bionest BNC-12	250 ATU								
01-011-65D-C4	4 C4	6.00	49.50				3300		10/31/2001	
REMARKS: House	s Bionest BNC-12	250 ATU. AA	SHTO HS2	0 traffic	loading rated	d when buri	ed between 18	8" to 48"		
01-011-68D-C	3 C3	4.00	54.00				3700		8/14/2001	
REMARKS: House	s Bionest BNC-15	500 ATU								
01-011-69D-C4	4 C4	6.00	55.00				3700		5/29/2002	
REMARKS: House	s Bionest BNC-15	500 ATU. AA	SHTO HS2	0 traffic	loading rated	d when buri	ed between 18	8" to 48"		
01-011-AK10-0	C3 C3	3.00	56.50	62	119		1342	1,583	8/12/2008	}
DEMARKS. House	es AquaKlear AK1	000C 1000 ga	allon per da	y ATU; t	wo notches	for 1/2" airli	ne on inlet sid	e		
KEIVIAKKS. HOUSE	o riqual tioul rict	9		•						



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Florida Septic,Inc.

ACTIVE

Post Office Box 545 Hawthorne, FL 32640

01-011-BM6-C3

01-011-BM7-C4

01-011-BM8-C4

01-011-BM9-C4

C3

C4

C4

REMARKS: Used to house Bio-Microbics MicroFAST 4.5F ATU C4

4.00

4.00

6.00

6.00

65.00

63.00

63.00

53.00

REMARKS: Used to house Bio-Microbics MicroFAST 1.5F or S ATU. Inlet and/or outlet can be 4" or 6".

102

78

Alachua

TOTAL

		WALL	LIQUID	TOP E	XTERIOR	IN-OUT	EFFECTIVE	GALLONS		APPROVAL	•
TANK NUMBER	CATEGORY	THICKNESS	DEPTH	WIDTH	LENGTH	DROP	GALLONS	(Pump Tanks) USE	DATE	FAMILY
01-011-AK5B-	C3 C3	3.00	50.50	81.38	139.5	2	1875	ļ	ATU	8/27/2007	
REMARKS: House	es AquaKlear <i>i</i>	AK5B3 500 gpd	ATU unit, v	which cor	ntains an Ak	(500C unit	with pretreatm	ent and dosing	g compa	rtments. Tw	o section lid.
01-011-AK8-C	:3 C3	3.00	57.50	57	103	2	1020	1,193 <i>A</i>	ATU	12/14/2005	
REMARKS: Used	to house Aqua	aKlear AK800C	gallon per o	day ATU;	two notches	s for 1/2" a	irline on inlet s	side.			
01-011-BM1-C	C3 C3	3.00	45.00				1100	1,479 A	ATU	10/31/2003	
REMARKS: Used	to house Bio-N	Microbics Micro	FAST 0.5FS	S ATU							
01-011-BM10-	C4 C4	6.00	66.00				2400			3/28/2012	
REMARKS: Conv	erted 02-05-20	12. Houses Bio	o-Microbics	MicroFA	ST 1.5 ATL	J. AASHT	O HS20 traffic	loading rated v	vhen bu	ried between	18" to 48"
01-011-BM11-	.C4 ^{C4}	6.00	66.00	106	194.75		4500	5,909 A	ATU	3/28/2012	
REMARKS: Used	to house Bio-N	Microbics Micro	FAST 3.0F	and 3.0F	S ATU. AA	ASHTO HS	20 traffic loadi	ng rated when	buried b	etween 18"	to 48"
01-011-BM12-	.C4 C4	6.00	65.00	106	194.75		4400	A	ATU	3/28/2012	
REMARKS: AASH	HTO HS20 traff	ic loading rated	l when burie	ed betwee	en 18" to 48	". Used to	house Bio-Mio	crobics MicroF	AST 4.5	F ATU	
01-011-BM2-C	C4 C4	4.00	53.00				1500	1,919 <i>A</i>	ATU	10/31/2003	
REMARKS: Used	to house Bio-N	Microbics Micro	FAST 0.5FS	S, 0.75FS	s, and 0.9FS	S ATU					
01-011-BM3-C	C4 C4	4.00	57.00				2150	2,752 A	ATU	10/31/2003	
REMARKS: Used											
TEMPTINO. OSCU	to house Bio-N	Microbics Micro	FAST 1.5FS	S ATU							
01-011-BM4-C		Microbics Micro 3.00	FAST 1.5FS 43.00				1600	2,433	ATU	10/31/2003	
01-011-BM4-C	C3	3.00	43.00		nd 0.9F ATI	J	1600	2,433 <i>A</i>	ATU	10/31/2003	;
	C3 to house Bio-N	3.00	43.00	0.75F, a	nd 0.9F ATI	J	1600 4500	2,433 A		10/31/2003	

REMARKS: Converted 01-011-27D-C4, to house Bio-Microbics MicroFAST .5, .75, and .9 ATU. AASHTO HS20 traffic loading rated when buried between 18" to 48"

190.75

154.5

154.5

REMARKS: (01-011-29S-C4 converted to ATU tank, 02-05-2012) Used to house Bio-Microbics MicroFAST 1.5 ATU with 750 gallon pretreatment tank.

4400

2400

2400

1500

5,913 ATU

3.021 ATU

3,021

2/17/2004

9/13/2007

3/1/2012



DEPARTMENT OF HEALTH STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Fuji Clean USA

41-2 Greenwood Road Brunswick ME 04011

		WALL	LIQUID		KTERIOR	IN-OUT	EFFECTIVE		APPROVAL
TANK NUMBER	CATEGORY	THICKNESS	DEPTH	WIDTH	LENGTH	DROP	GALLONS	(Pump Tanks) US	E DATE FAMILY
70-154-CE10-0	C3 C3	0.15	59.00	56.25	98.375	2	1069	ATU	11/19/2015
REMARKS: Used	to house Fuji (Clean USA CE1	0 900 gpd	ATU; no	mid-seam te	esting requi	ired		
70-154-CE14-	C3 C3	0.12	59.50	69	119	2.5	1498	ATU	5/10/2016
REMARKS: Used	to house Fuji (Clean USA CE1	4 1000 gpc	ATU; no	mid-seam	testing requ	uired		
70-154-CE21-	C3 C3	0.12	63.25	72	152.75	2	2252	2,536 ATU	5/10/2016
REMARKS: Used	to house Fuji (Clean USA CE2	1 1800 gpc	ATU; no	mid-seam	testing requ	uired		
70-154-CE30-	C3 C3	0.12	68.88	77.75	183	2.125	3199	3,435 ATU	5/10/2016
REMARKS: Used	to house Fuji (Clean USA CE3	0 2700 gpd	ATU; no	mid-seam	testing req	uired		
70-154-CE5-C	3 C3	0.12	47.25	43.25	84.625	1.6	540	ATU	11/19/2015
REMARKS: Used	to house Fuji (Clean USA CE5	450 gpd A	TU; no m	id-seam tes	sting require	ed		
70-154-CE7-C	3 C3	0.12	50.88	48.25	94.75	2	749	ATU	11/19/2015
REMARKS: Used	to house Fuji (Clean USA CE7	630 gpd A	TU; no m	id-seam tes	sting require	ed		
70-154-CEN10)-C3 ^{C3}	0.12	59.50	69	119	2.5	1498	ATU	11/19/2015
REMARKS: Used	to house Fuji (Clean USA CEN	110 900 gpd	d ATU; no	o mid-seam	testing req	uired		
70-154-CEN5-	C3 C3	0.12	50.88	48.25	94.75	2	749	ATU	11/19/2015
REMARKS: Used	to house Fuji (Clean USA CEN	15 450 gpd	ATU; no	mid-seam to	esting requ	ired		
70-154-CEN7-	C3 C3	0.15	59.00	56.25	98.375	2	1069	ATU	11/19/2015
REMARKS: Used		Clean USA CEN	17 630 gpd	ATU; no	mid-seam to	esting requ	ired		



Naples FL 34106

DEPARTMENT OF HEALTH

STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

George W.Shepard & Son, Inc.

Collier

PO Box 202 ACTIVE

TOTAL

		WALL	LIQUID	TOP EX	KTERIOR	IN-OUT	EFFECTIVE	GALLONS	APPROVAL	
ANK NUMBER	CATEGORY	THICKNESS	DEPTH	WIDTH	LENGTH	DROP	GALLONS	(Pump Tanks) USE	DATE F	AMILY
11-149-H10G-	-C4 C4	2.50	65.00	89	89	1.25	1880	2,100 ATU	2/26/2014	1
REMARKS: Hous	es the Hoot 10	00 gpd gravity A	ATU system	(H-1000	A), require	s 700-1500	gal pretreatm	ent tank; 5000 psi cor	ncrete	
11-149-H10G-	-C3 C3	2.50	65.00	89	89	1.25	1880	2,100 ATU	2/26/2014	1
REMARKS: Hous	es the Hoot 10	00 gpd gravity A	ATU system	(H-1000	A), require	s 700-1500	gal pretreatm	ent tank		
11-149-H10P-	C3 C3	2.50	65.00	89	157		3309	ATU	10/25/2011	1
REMARKS: Hous	es the Hoot 10	00 gpd dosed A	TU system	(H-1000	AND),requi	res 700-15	00 gal pretrea	tment tank		
11-149-H10P-	C4 C4	2.50	65.00	89	157		3309	ATU	4/3/2012	1
REMARKS: Hous	es the Hoot 10	00 gpd dosed A	TU system	(H-1000	AND), requ	ires 700-1	500 gal pretrea	tment tank; 5000 psi	concrete	
11-149-H6G-0	C3 C3	2.50	52.00	74.5	106		1320	ATU	10/24/2011	3
REMARKS: Hous	es either the H	oot 500 or 600 (gpd gravity	flow ATL	J (H-500A; H	l-600A)				
11-149-H6G-0	C4 C4	2.50	52.00	74.5	106		1320	ATU	7/12/2012	8
REMARKS: Hous	es either the H	oot 500 or 600 (gpd gravity	flow ATL	J (H-500A; F	H-600A); 50	000 psi concre	te		
11-149-H6P-C	C4 C4	2.50	52.00	74.5	160		2080	ATU	7/12/2012	8
REMARKS: Hous		oot 500 or 600 (gpd dosed A	ATU (H-5	600 AND, H-	600 AND).	Needs recircu	ılation for increased ni	trogen reduction	on; 5000 ps
11-149-H6P-C	C3 C3	2.50	52.00	74.5	160		2080	ATU	10/25/2011	2
REMARKS: Hous	es either the H	oot 500 or 600 g	gpd dosed A	ATU (H-5	600 AND, H-	600 AND).	Needs recircu	ation for increased nit	rogen reduction	n



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

H.G. McGrew, Inc.

REMARKS: Used to house the Mighty Mac 600 ATU

3805 Industrial Drive Bossier City LA 71112

_	A		

Dossier Oity EA 71	112							TOTAL				
		WALL	LIQUID	TOP E	XTERIOR	IN-OUT	EFFECTIVE	GALLONS	A	APPROVAL	_	
TANK NUMBER	CATEGORY	THICKNESS	DEPTH	WIDTH	LENGTH	DROP	GALLONS	(Pump Tanks)	USE	DATE	FAMILY	
70-121-MM1-C	4 C4	0.38	66.00					A	ΓU	3/22/2002	2	
REMARKS: Used t	o house the N	lighty Mac 500	ATU									
70-121-MM2-C	3 C3	0.38	66.00					A ⁻	ΓU	10/6/2002	2	
REMARKS: Used t	o house the N	lighty Mac 750	ATU									
70-121-MM3-C	3 C3	0.38	66.00					A ⁻	ΓU	10/6/2002)	



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Howie Concrete Products, Inc.

Monroe

2817 Central Avenue Big Pine Key, FL 33043

44-085-NW3-C3

Active

3,							TOTAL			
		WALL	LIQUID	TOP EXTERIOR	IN-OUT	EFFECTIVE	GALLONS	AF	PPROVAL	ı
TANK NUMBER	CATEGORY	THICKNESS	DEPTH W	VIDTH LENGTI	H DROP	GALLONS	(Pump Tanks)	USE	DATE	FAMILY
44-085-08D-C	3 C3	2.50	41.00			900			1/23/2004	
REMARKS: House	es the Bio-Mic	robics MicroFAS	ST 0.5F short	ATU. Houses .2	250 and .37	'5 RetroFASTu	nits as Alternativ	e Drainfi	eld Repair	
44-085-11D-C	3 C3	2.50	41.00			1050			1/23/2004	
REMARKS: House	es the Bio-Mic	robics MicroFAS	ST 0.5F short	ATU. Houses .2	250 and .37	5 RetroFASTu	nits as Alternativ	e Drainfi	eld Repair.	
44-085-NW1-0	C3 C3	2.50	54.00						3/22/2002	
DE144 D140	(0)			=00/000						4000 !!

REMARKS: Norweco (Singulair 960 and Singulair TNT model) 500/600 gallon per day ATU. Add 1000 gallon pretreatment chamber to become 1000 gallon per day ATU.

44-085-NW2-C3 C3 2.50 66.00 3/22/2002

REMARKS: Norweco (Singulair 960 and Singulair TNT model) 750/800 gallon per day ATU. Add 1250 pretreatment chamber to become 1250 gallon per day ATU.

REMARKS: Norweco (Singulair 960 and Singulair TNT model) 1500 gallon per day ATU (requires minimum 1500 gallon pretreatment tank)

2.50

78.00



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Hydro-Action

2055 Pidco Drive Plymouth IN 46563

TANK NUMBER	CATEGORY	WALL THICKNESS		TOP EXTERIOR WIDTH LENGTH	IN-OUT DROP	EFFECTIVE GALLONS	GALLONS (Pump Tanks) USE	APPROVAL DATE FAMILY
70-118-HA1-C	:3 C3	0.25	64.00				ATU	9/24/2002
REMARKS: 500 g	allon per day A	TU tank-fiberg	lass					
70-118-HA2-C	3 C3	0.25	64.00				ATU	9/24/2002
REMARKS: 600 g	allon per day A	TU tank-fiberg	lass					
70-118-HA3-C	3 C3	0.31	64.00				ATU	9/24/2002
REMARKS: 750 g	allon per day A	TU tank-fiberg	lass					
70-118-HA4-C	:3 C3	0.38	70.00				ATU	9/24/2002
REMARKS: 1000	gallon per day	ATU tank-fiber	glass					
70-118-HA5-C	.3 C3	0.38	80.00				ATU	9/24/2002
REMARKS: 1500	gallon per day	ATU tank-fiber	glass					



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Infiltrator Water Technologies, LLC

4 Business Park Road; P.O. Box 768

Old Saybrook, CT	06475							TOTAL		
TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EX	CTERIOR LENGTH	IN-OUT DROP	EFFECTIVE GALLONS	GALLONS (Pump Tanks)		PPROVAL DATE FAMILY
70-143-BM5S-	.C3 C3	0.20	44.00	58	119	3	1090	1,280 AT	Ū	1/7/2016
REMARKS: single	compartment	PP tank, two ve	ertical stiffe	ners. Hou	uses MF 0.5	ATU. Red	uires at least	350 gal pretreatm	nent tan	k. IM-1060
70-143-BM6S-	-C3 C3	0.20	44.00	58	119	3	1090	1,280 AT	Ū	1/7/2016
REMARKS: single	compartment	PP tank, two ve	ertical stiffe	ners. Hou	uses MF 0.6	25 ATU. F	equires at lea	st 375 gal pretrea	atment t	ank. IM-1060
70-143-BM7S-	-C3 C3	0.20	44.00	58	119	3	1090	1,280 AT	Ū	1/7/2016
REMARKS: single	compartment	PP tank, two ve	ertical stiffe	ners. Hou	uses MF 0.7	′5 ATU. Re	quires at leas	t 375 gal pretreat	ment ta	nk. IM-1060



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Mack Concrete Industries

Post Office Box 157 Astatula, FL 34705

Lake

ACTIVE

Astatula, FL 3470	•							TOTAL			
		WALL	LIQUID	TOP EX	TERIOR	IN-OUT	EFFECTIVE	GALLONS	Α	PPROVA	L
TANK NUMBER	CATEGORY	THICKNESS	DEPTH	WIDTH	LENGTH	DROP	GALLONS	(Pump Tanks)	USE	DATE	FAMILY
35-015-08D-C	3 C3	2.50	42.00				1050			3/22/200	2
REMARKS: House	es Rionest RNI	C-400 ATLI									

35-015-08D-C3	03	2.30	42.00			1030		3/22/2002
REMARKS: Houses Bio	nest BNC-40	OO ATU						
35-015-15D-C3	C3	3.00	48.00			1500		3/22/2002
REMARKS: Houses Bio	nest BNC-50	00 ATU and 6	00 ATU					
35-015-30D-C3	C3	3.00	48.00			2000		3/22/2002
REMARKS: Houses Bio	nest BNC-75	50 ATU						
35-015-64D-C3	C3	4.00	42.00			3500		3/22/2002
REMARKS: Houses Bio	nest BNC-12	250 ATU						
35-015-72D-C3	C3	4.00	51.00			4300		3/22/2002
REMARKS: Houses Bio	nest BNC-15	500 ATU						
35-015-CA1-C3	C3	2.50	55.00	62	94		ATU	9/18/2008
REMARKS: CajunAire 5	i00 gallon pe	er day ATU						
35-015-NW1-C3	C3	2.50	54.00					3/22/2002
REMARKS: Norweco (S per day ATU	•	and Singulair	TNT mode	1) 500/600) gallon per day	ATU. Add 1000 gallon p	retreatment ch	amber to become 1000 gallo

2.20 66.00 C3 3/22/2002 35-015-NW2-C3

REMARKS: Norweco (Singulair 960 and Singulair TNT model) 750/800 gallon per day ATU. Add 1250 pretreatment chamber to become 1250 gallon per day ATU.

2.50 78.00 3/22/2002 35-015-NW3-C3

REMARKS: Norweco (Singulair 960 and Singulair TNT model) 1500 gallon per day ATU (requires minimum 1500 gallon pretreatment tank)



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Murrill Tank Service, Inc.

3621 Alab Club Road

Mobile AL 36605

TOTAL	

	WALL	LIQUID	TOP EX	<u>XTERIOR</u>	IN-OUT	EFFECTIVE	GALLONS	Α	PPROVA	<u>L</u>
TANK NUMBER	CATEGORY THICKNESS	DEPTH	WIDTH	LENGTH	DROP	GALLONS	(Pump Tanks)	USE	DATE	FAMILY

68-135-H10P-C4	C4	2.50	64.00	ATU	8/3/2007
REMARKS: Houses the H	Hoot 1000 gp	d dosed ATI	J system; requires 700-1500 gal pretreatment tank		
68-135-H6G-C3	C3	2.50	52.00	ATU	1/8/2007
REMARKS: Houses either	er the Hoot 50	00 or 600 gp	d gravity flow ATU system.		
68-135-H6P-C3	C3	2.50	52.00	ATU	1/8/2007
REMARKS: Houses either	er the Hoot 50	00 or 600 gp	d dosed or drip irrigation ATU system		



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Norweco

220 Republic Street Norwalk OH 44857-1156 **ACTIVE**

TOTAL	

WALL IN-OUT EFFECTIVE GALLONS **APPROVAL** LIQUID **TOP EXTERIOR**

TANK NUMBER **CATEGORY THICKNESS** DEPTH WIDTH LENGTH DROP GALLONS (Pump Tanks) USE DATE FAMILY

70-150-NW1-C3 0.38 52.00 125.5 1280 1,430 ATU 11/17/2011

REMARKS: Polyethylene tank; three joined compartments; used to house ATU Norweco Singulair Green 960-500 or TNT-500, NSF-40 certified for 500 and 600 gpd; length revised 10/27/2016



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Orenco Systems, Incorporated

814 Airway Avenue ACTIVE

Sutherlin Or 97479

TOTAL

WALL	LIQUID	TOP EXTERIOR	IN-OUT	EFFECTIVE GALLONS	APPROVAL
------	--------	--------------	--------	-------------------	----------

TANK NUMBER CATEGORY THICKNESS DEPTH WIDTH LENGTH DROP GALLONS (Pump Tanks) USE DATE FAMILY

70-128-AXRT1-C3 C3 5/24/2010

REMARKS: Fiberglass recirculating tank used to house Advantex AX20-RT as part of a 500 gpd ATU, requires 1000 gal minimum pretreatment tank.

70-128-X100-C3 C3 11/28/2006

REMARKS: Fiberglass tank used to house AdvanTex AX100 treatment media as part of a 2000 gpd ATU.

70-128-X20-C3 ^{C3} 8/30/2004

REMARKS: Fiberglass tank used to house AdvanTex AX20 treatment media as part of a 500 gpd ATU.



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Premier Tech

1, Avenue Premier Quebec G5R 6CI C **ACTIVE**

TOTAL

WALL LIQUID <u>TOP EXTERIOR</u> IN-OUT EFFECTIVE GALLONS APPROVAL
TANK NUMBER CATEGORY THICKNESS DEPTH WIDTH LENGTH DROP GALLONS (Pump Tanks) USE DATE FAMILY

70-124-650-C3 C3 49.00 4/3/2003

REMARKS: Fiberglass tank-Used to house the STB-650 EcoFlo peat biofilter ATU



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Quanics

3244 Old LaGrange Road Crestwood KY 40014

								TOTAL		
TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EX	KTERIOR LENGTH	IN-OUT DROP	EFFECTIVE GALLONS	GALLONS (Pump Tanks)	APPROVA DATE	L FAMILY
70-116-01-C3	C3	0.25	30.00						8/29/200	2
REMARKS: ATS-S	CAT-200 (200) gallon per day	ATU) fiber	glass						
70-116-02-C3	C3	0.25	30.00						8/29/200	2
REMARKS: ATS-S	CAT-400 (400) gallon per day	ATU) fiber	glass						
70-116-03-C3	C3	0.25	30.00						8/29/200	2
REMARKS: ATS-S	CAT-650 (650) gallon per day	ATU) fiber	glass						
70-116-04-C3	C3	0.25	30.00						8/29/200	2
REMARKS: ATS-S	CAT-1050 (10	050 gallon per o	lay ATU) fib	erglass						
70-116-08-C3	C3	0.31		96	198		3000		9/8/201	0
REMARKS: Fiberg	lass (FRP) Ho	uses 5000 gpd	Quanics A	erocell or	· Bio-COIR	ATU media	a			



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS

SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Rick's Pre Fab

25525 SW 141st Ave. Princeton, FL 33032

Dade

ACTIVE

TOTAL EFFECTIVE GALLONS

WALL LIQUID IN-OUT **APPROVAL TOP EXTERIOR TANK NUMBER CATEGORY THICKNESS DEPTH WIDTH LENGTH** DROP GALLONS (Pump Tanks) USE DATE FAMILY

3.00 51.00 13-045-04S-C3 3/22/2002 REMARKS: Also houses Bio-Microbics MicroFAST 0.5 ATU, when used with a 350 gallon min. settling tank; RTF 0.25 and RTF 0.375 as Alternative Drainfield Repair 1050 3.00 51.00 1/3/2007 13-045-08S-C3 Also houses Bio-Microbics MicroFAST 0.5 ATU, when used with a 350 gallon min. settling tank. Houses RTF 0.25, RTF 0.375 as Alternative REMARKS: Drainfield Repair. Also houses MF 0.75, MF 0.9 ATU when used with 500 gallons min. settling tank. Can house HS 1.0 with 500 pretreatment 13-045-12S-C3 C3 3.13 51.00 1200 3/22/2002 REMARKS: Also houses RetroFAST 0.25 and 0.375 as Alternative Drainfield Repair. Houses Bio-Microbics MicroFAST 0.5 ATU when used with 350 gallon min. settling tank, MF 0.75, MF 0.9 ATU, when used with 500 gallons min. settling tank. Can house HS 1.0 with 500 pretreatment tank. Also houses Bio-Microbics MF 1.5 ATU when used with 750 gallons min. settling tank. C3 3.13 51.00 1350 3/22/2002 13-045-16S-C3 REMARKS: Also houses Bio-MicroFAST 0.5 ATU, when used with 350 gallons min. settling tank; MicroFAST 0.75, 0.9 ATU when used with 500 gallons min settling tank. Can house HS 1.0. Also houses MF 1.5 ATU with 750 settling tank.

3 13 51.00 3/22/2002 13-045-20S-C3

REMARKS: Also houses Bio-Microbics MicroFAST 0.5 ATU when used with 350 gallon min settling tank; MicroFAST 0.75 and 0.9 ATU when used with 500 gallon min settling tank. Can house HS 1.0. Also houses MicroFAST 1.5 ATU with 750 gallons min. settling tank.

4.00 51.00 8/19/2009 13-045-21S-C3

REMARKS: H10 traffic rating. Also houses Bio-Microbics MicroFAST 0.5 ATU, when used with a 350 gallon min. settling tank; RetroFAST 0.25 and 0.375 as Alternative Drainfield Repair

4.00 51.00 1050 8/19/2009 13-045-22S-C3

H10 traffic rating. Also houses Bio-Microbics MicroFAST 0.5 ATU, when used with a 350 gallon min. settling tank. Houses RetroFAST 0.25 and 0.375 as Alternative Drainfield Repair. Also houses MicroFAST 0.75 and 0.9 ATU when used with 500 gallons min, settling tank. Can house HS 1.0 with 500 pretreatment tank

C34.00 51.00 104 8/19/2009 13-045-23S-C3

REMARKS: H10 traffic rating. Also houses RTF 0.25, RTF 0.375 as Alternative Drainfield Repair. Houses Bio-Microbics MicroFAST 0.5 ATU when used with 350 gallon min. settling tank; MicroFAST 0.75 and 0.9 ATU, when used with 500 gallons min. settling tank. Can house HS 1.0 with 500 pretreatment tank. Also houses Bio-Microbics MicroFAST 1.5 ATU when used with 750 gallons min. settling tank.

4.00 51.00 1500 C3 73 122 8/19/2009 13-045-24S-C3

REMARKS: H10 traffic rating. Also houses Bio-Microbics MicroFAST 0.5 ATU when used with 350 gallon min settling tank; MicroFAST 0.75 and 0.9 ATU when used with 500 gallon min settling tank. Can house HS 1.0. Also houses MicroFAST 1.5 ATU with 750 gallons min. settling tank

51.00 96 6.00 13-045-31S-C4 9/22/2009

REMARKS: HS20 traffic rating. Also houses Bio-Microbics MicroFAST 0.5 ATU, when used with a 350 gallon min. settling tank; RetroFAST 0.25 and 0.375 as

Alternative Drainfield Repair

6.00 51.00 66 110 1050 9/22/2009 13-045-32S-C4

REMARKS: HS20 traffic rating. Also houses Bio-Microbics MicroFAST 0.5 ATU, when used with a 350 gallon min. settling tank. Houses RetroFAST 0.25 and 0.375 as Alternative Drainfield Repair. Also houses MicroFAST 0.75, 0.9 ATU when used with 500 gallons min. settling tank. Can house HS 1.0

with 500 pretreatment tank

C4 6.00 51.00 74 108 1200 13-045-33S-C4 9/22/2009

REMARKS: HS20 traffic rating. Also houses RetroFAST 0.25, 0.375 as Alternative Drainfield Repair. Houses Bio-Microbics MicroFAST 0.5 ATU when used with 350 gallon min. settling tank; MicroFAST 0.75, 0.9 ATU, when used with 500 gallons min. settling tank. Can house HS 1.0 with 500 pretreatment tank. Also houses Bio-Microbics MicroFAST 1.5 ATU when used with 750 gallons min. settling tank.



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016

un date: 11/9/2016 Searching for: ATU

Rick's Pre Fab

25525 SW 141st Ave. Princeton, FL 33032 Dade

ACTIVE

TOTAL

WALL LIQUID TOP EXTERIOR IN-OUT EFFECTIVE GALLONS APPROVAL

TANK NUMBER CATEGORY THICKNESS DEPTH WIDTH LENGTH DROP GALLONS (Pump Tanks) USE DATE FAMILY

13-045-34S-C4 C4 6.00 51.00 77 126 1500 9/22/2009

REMARKS: HS20 traffic rating. Also houses Bio-Microbics MicroFAST 0.5 ATU when used with 350 gallon min settling tank; MicroFAST 0.75, MicroFAST 0.9 ATU when used with 500 gallon min settling tank. Can house HS 1.0. Also houses MF 1.5 ATU with 750 gallons min. settling tank



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS

SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Sebring Septic Tank & Precast Co. Inc.

Highlands

8037 Commercial Blvd.

REMARKS: Aqua Aire 1200 gallon per day ATU

Sebring FL 33870	Divu.							7.011	.	
3		WALL	LIQUID '	TOP EXT	TERIOR	IN-OUT	EFFECTIVE	TOTAL GALLONS	APPROVAL	
TANK NUMBER	CATEGORY		DEPTH W			DROP		(Pump Tanks)	USE DATE	FAMILY
28-O15-03D-0	C4 C4	3.00	55.00				1050		11/9/2001	
REMARKS: Hous	es Bionest BNC	-400 ATU. Mo	nolithic baffl	е						
28-O15-06D-0	C4 C4	3.00	49.50				1250		11/9/2001	
REMARKS: Hous	es Bionest BNC	-500 ATU. Mo	nolithic baffl	е						
28-O15-08D-0	C3 C3	3.00	53.30				1050		11/9/2001	
REMARKS: Hous	es Bionest BNC	-400 ATU. Als	o available	in 4" and	d 6" thick w	vall tanks				
28-O15-10D-C	C4 C4	6.00	53.30				1050		4/22/2002	
REMARKS: Hous	es Bionest BNC	-400 ATU. H	IS20 traffic	rated						
28-O15-16D-C	C3 C3	3.00	57.80				1250		4/22/2002	
REMARKS: Hous	es Bionest BNC	-500 ATU; slide	-in baffle							
28-O15-17D-0	C3 C3	4.00	57.80				1250		8/2/2002	
REMARKS: Hous	es Bionest BNC	-500 ATU; slide	-in baffle							
28-O15-19D-C	C3 C3	3.00	44.00	68	145	1	1500	1,800 b	4/22/2002	
REMARKS: Hous	es Bionest BNC	-600 ATU. Mo	nolithic baffl	е						
28-O15-24D-0	C4 C4	6.00	42.00	90	130		1500		4/22/2002	
REMARKS: w/o s traffic	lide-in baffle, ca rated	n house Bio-Mic	crobics MF 1	1.5 1,500	gpd ATU	when use	d with 750 gallo	on min pretreatm	nent tank (02/26/10)	HS20
28-O15-24S-C	C4 C4	6.00	42.00	90	130		1500		4/22/2002	
REMARKS: Can h	nouse Bio-Micro	bics MF 1.5 1,50	00 gpd ATU	when us	sed with 75	50 gallon n	nin pretreatme	nt tank (02/26/10). HS20 traffic ra	ted
28-O15-34D-C	C4 C4	6.00	56.00				2000		4/22/2002	
REMARKS: Hous	es Bionest BNC	-750 ATU.	HS20 tr	affic rate	ed					
28-O15-35D-0	C4 C4	4.00	55.50				2000	2,455	11/19/2004	
REMARKS: Hous	es Bionest BNC	-750 ATU.								
28-O15-46D-C	C4 C4	6.00	70.00				2500		12/12/2000	
REMARKS: Hous	es Bionest BNC	-1000 ATU.	HS20 traf	fic rated						
28-O15-AA1-0	C3 C3	2.50	52.50	0	0		500		6/30/2006	
REMARKS: Aqua	Aire 500 gallon	per day ATU								
28-O15-AA2-0	C3 C3	2.50	54.00	0	0		800		10/5/2006	
REMARKS: Aqua		per day ATU								
28-O15-AA3-0	C3 C3	2.50	52.00	0	0		600		4/13/2007	
REMARKS: Aqua		per day ATU								
28-O15-AA4-0	C3 C3	2.50	52.00	74	114		1000		5/7/2008	
REMARKS: Aqua	Aire 1000 gallor	n per day ATU								
28-O15-AA5-0	C3 C3	2.50		0	0				8/25/2010	



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Sebring Septic Tank & Precast Co. Inc.

Highlands

8037 Commercial Blvd. Sebring FL 33870

per day ATU.

9							TOTAL	
TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR WIDTH LENGTH	IN-OUT DROP	EFFECTIVE GALLONS		Y
28-O15-AW1-0	C3 C3	2.50	52.00			500	8/19/2003	
REMARKS: Ameri	can Wastewat	er 500 gallon p	er day B.E.	S.T. 1 ATU				
28-O15-AW2-0	C3 C3	2.50	54.00			800	2/3/2004	
REMARKS: Ameri	can Wastewat	er 800 gallon p	er day B.E.	S.T. 1 ATU				
28-O15-AW3-0	C3 C3	2.50	82.00			1200	2/3/2004	
REMARKS: Ameri	can Wastewat	er 1200 gallon	per day B.E	S.T. 1 ATU				
28-O15-AW4-0	C3 C3	2.50	61.00	0 0		1000	6/30/2006	
REMARKS: Ameri	can Wastewat	er 1000 gallon	per day B.E	S.T. 1 ATU				
28-O15-NW1-0	C3 C3	2.50	51.00				8/23/2002	
REMARKS: Norwe	eco (Singulair 9	960 and Singula	air TNT mod	del) 500/600 gallon p	er day ATI	J. Add 1000 g	gallon pretreatment chamber to become 100	00 gallo



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Southeastern Septic, LLC

Polk

2060

Active

ATU

8/21/2013

Eaton Park FL 33840

53-152-H6P-C3

PO Box 2541

TOTAL

WALL LIQUID <u>TOP EXTERIOR</u> IN-OUT EFFECTIVE GALLONS APPROVAL

TANK NUMBER CATEGORY THICKNESS DEPTH WIDTH LENGTH DROP GALLONS (Pump Tanks) USE DATE FAMILY

160

REMARKS: houses Hoot 500 or 600 gpd dosed ATU (H-500 AND, H-600 AND). Needs recirculation for increased nitrogen reduction.

74.5

52.00



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016 Searching for: ATU

Southern Precast, Inc. (Moultrie, GA)

450-C GA Hwy 33 S

Moultrie, GA 31788

TOTAL

	WALL	LIQUID	TOP EXTERIOR	IN-OUT	EFFECTIVE	GALLONS	Α	PPROVA	L
TANK NUMBER	CATEGORY THICKNESS	DEPTH	WIDTH LENGTH	DROP	GALLONS	(Pump Tanks)	USE	DATE	FAMILY

44.00 101.75 1050 1,200 3/22/2002 69-070-08D-C3 REMARKS: slide-in baffle; w/o slide-in baffle also approved: to house BIO-Microbics MF 0.5 ATU, when used with 350gallon min. settling tank; BM MF 0.75 &MF 0.9 ATU when used with a 500 gallon min. settling tank. 2.50 101.75 1050 44.00 1,200 69-070-08S-C3 REMARKS: Also approved to house BIO-Microbics MF 0.5 ATU, when used with 350gallon min. settling tank; BM MF 0.75 &MF 0.9 ATU when used with a 500 gallon min. settling tank.

69-070-NW1-C3 C3 3.00 41.00 72 146 ATU 10/2/2007

REMARKS: Norweco (Singulair 960 and Singulair TNT model) 500/600 gallon per day ATU. Also 1000 Gallon per day ATU with 1000 gallon pretreatment tank.



STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS SEPTIC TANK MANUFACTURERS

run date: 11/9/2016

Searching for: ATU

Third Generation Plumbing

3980 Overseas Highway Marathon FL 33050 Monroe

ACTIVE

050	J50			TOTAL				
	WΔII	LIQUID	TOP EXTERIOR	IN-OUT	FFFCTIVE GALLONS	APPROVAL		

TANK NUMBER CATEGORY THICKNESS DEPTH WIDTH LENGTH DROP GALLONS (Pump Tanks) USE DATE FAMILY

44-122-05-C3	C3	3.00	54.00	ATU	1/27/2003
REMARKS: Used to house	e the 500 gallo	on per day A	AquaKlear ATU.		
44-122-07-C3	C3	3.00	61.00	ATU	5/2/2003
REMARKS: Used to house	e the 750 gallo	n per day A	AquaKlear ATU		
44-122-08-C3	C3	3.00	61.00	ATU	7/27/2004
REMARKS: Used to house	e the 800 gallo	n per day A	AquaKlear ATU		